



## TECHNICAL DETAILS FOR THE GC-V PRESS SERIES



# HIGGINS BALERS LTD

RENEWING, REPAIRING, REPLACING

TECHNICAL FEATURES	GC-V-210-A		GC-V-280-A		GC-V-310-A		GC-V-330-A	
CHARGE BOX (mm)	2400x1250x730		2500x1250x830		3800x1500x1300		2850x1250x1165	
BALE SIZE (mm)	300x300		400x400		600x600		400x400	
MOTOR POWER (kW)	2 x 55		2 x 75		2 x 90		2 x 90	
CYLINDER FORCE (tonnes)	95/170/185		115/195/250		140/250/280		150/270/300	
SPECIFIC PRESSURE (kg/cm <sup>2</sup> )	205		156		77		187	
BALE WEIGHT (kg)	70	120	160	260	415	550	200	250
PRODUCTION:								
(Bales/h)	109	120	102	112	80	87	95	102
MIN - MAX (kg/h) Steel	7,630	10,740	16,320	22,220	33,200	40,052	19,000	22,075
MIN - MAX (kg/h) Copper	11,445	16,110	24,480	33,330	49,800	60,078	28,500	33,112
MIN - MAX (kg/h) Aluminium	2,543	3,580	5,440	7,406	11,066	13,350	6,333	7,358
AVERAGE (kg/h) Steel	7,807		16,379		31,132		17,457	
AVERAGE (kg/h) Copper	11,711		24,569		46,698		26,185	
AVERAGE (kg/h) Aluminium	2,602		5,460		13,377		5,819	

